



サイズNo.	溝底r(最大)
7未満	0.13
7~12未満	0.25
12以上	0.38

単位:mm

サイズNo.	止 め 輪				適 用 す る 軸										
	d	D	t	V	d ₁		d ₂		m		X		n		
					基本寸法	公差	基本寸法	公差	基本寸法	公差	最小	最大	最小		
BETW-	1.5	1.5	4	0.4	0.8	+0.15	2	2.5	1.53	+0.06	0.8	+0.1	0.55	0.65	0.8
	2	2	5	0.4	0.8	-0.1	2.5	3.2	2.05	0	0.8		0.55	0.65	1
	2.5	2.5	6	0.4	0.8		3.2	4	2.55		0.8		0.55	0.65	1
	3	3	7	0.6	1.1	+0.25	4	5	3.05		1.1		0.85	1	1
	4	4	9	0.6	1.1	0	5	7	4.05	+0.075	1.1		0.85	1	1.2
	5	5	11	0.6	1.1		6	8	5.05	0	1.1		0.85	1	1.2
	6	6	12	0.8	1.3		7	9	6.05		1.3		1	1.2	1.2
	7	7	14	0.8	1.3	+0.4	8	11	7.1		1.3		1	1.2	1.5
	8	8	16	0.8	1.3	0	9	12	8.1	+0.09	1.3		1	1.2	1.8
	9	9	18	0.8	1.3		10	14	9.1	0	1.3		1	1.2	2
	10	10	20	1	1.7		11	15	10.15		1.7		1.3	1.6	2
	12	12	23	1	1.7		13	18	12.15	+0.11	1.7		1.3	1.6	2.5
	15	15	29	1.5	2.3	+0.8	16	24	15.15	0	2.3		1.8	2.2	3

材質:ばね用鋼 硬さ:40~50HRC 表面処理:亜鉛めっき3価クロメート

注意点

1. 受注生産品となります。