



単位:mm

サイズNo.	d		D		H (重荷重用)				L (軽荷重用)				
	基本寸法	公差	基本寸法	公差	t		h (約)	h+t (約)	t		h (約)	h+t (約)	
DB-	4	4.2	8	±0.3	0.4	±0.03	0.2	0.6	0.3	±0.025	0.25	0.55	
	5	5.2			0.5		0.75	0.4	0.3		0.7		
	6	6.2			12.5	±0.04	0.7	0.3	1	0.5	±0.03	0.35	0.85
	7	7.2			14		0.8	0.3	1.1	0.5		0.4	0.9
	8	8.2			16	±0.05	0.9	±0.04	0.35	1.25	0.6	±0.04	0.45
	9	9.2	18	1	0.4		1.4		0.7	0.5	1.2		
	10	10.2	20	1	0.45		1.45		0.8	0.55	1.35		
	11	11.2	22.5	±0.06	1.2	±0.05	0.5	1.7	0.8	±0.05	0.65	1.45	
	12	12.2	25		1.5		0.55	2.05	0.9		0.7	1.6	
	14	14.2	28	±0.07	1.5	±0.06	0.65	2.15	1	±0.05	0.8	1.8	
	16	16.3	31.5		1.75		0.7	2.45	1.2		0.9	2.1	
	18	18.3	35.5		2		0.8	2.8	1.2		1	2.2	
	20	20.4	40		2		0.9	2.9	1.5		1.15	2.65	
	22	22.4	45	±0.08	2.5	±0.07	1	3.5	1.75	±0.06	1.3	3.05	
	25	25.4	50		3		1.1	4.1	2		1.4	3.4	
	28	28.5	56	±0.09	3	±0.07	1.3	4.3	2	±0.07	1.6	3.6	
	30	31	63		3.5		1.4	4.9	2.5		1.75	4.25	
	35	36	71		4		1.6	5.6	2.5		2	4.5	
	40	41	80	±0.08	5	±0.08	1.7	6.7	3	±0.08	2.3	5.3	
	45	46	91		5		2	7	3.5		2.5	6	
50	51	100	±0.7	±0.7	6	±0.15	2.2	8.2	3.5	±0.09	2.8	6.3	

材質:ばね用鋼 硬さ:40~50HRC 表面処理:ACP(磷酸塩被膜)

注意点

1. 市場性の無い製品は在庫が無い場合があります。ご採用の際は事前にご確認ください。